



Bypass/restrictive, fixed-orifice, priority flow controls take an input flow at port 1 and use it to satisfy the priority flow at port 3. If the input flow exceeds the priority flow requirement, the excess is bypassed out port 2. The bypass flow may be used in a secondary circuit.

CONFIGURATION

L	Control	Tuning Adjustment
A	Setting Range	Replaceable Orifice .1 - 6 gpm (0,4 - 23 L/min.)
N	Seal Material	Buna-N
(none)	Material/Coating	Standard Material/Coating

TECHNICAL DATA

NOTAR: LOS DATOS PUEDEN VARIAR SEGÚN LA CONFIGURACIÓN . CONSULTE LA SECCIÓN DE CONFIGURATION

Maximum Operating Pressure	350 bar
Maximum Input Flow	60 L/min.
Locknut Hex Size	15 mm
Locknut Torque	9 - 10 Nm
Seal kit - Cartridge	Buna: 990011007
Seal kit - Cartridge	Polyurethane: 990011002
Seal kit - Cartridge	Viton: 990011006

CONFIGURATION OPTIONS

Model Code Example: FRCALAN

CONTROL	(L) SETTING RANGE	(A) SEAL MATERIAL	(N) MATERIAL/COATING
L Tuning Adjustment K manilla X Not Adjustable	A Replaceable Orifice .1 - 6 gpm (0,4 - 23 L/min.)	N Buna-N V Viton	Standard Material/Coating /AP Stainless Steel, Passivated