



Pilot-operated, pressure reducing valves reduce a high primary pressure at the inlet (port 2) to a constant reduced pressure at port 1, allowing circuits with multiple pressure requirements to be operated using a single pump.

### CONFIGURATION

<b>M</b>	Control	Capped Screw Adjustment with Lockwire Holes
<b>B</b>	Adjustment Range	50 - 1500 psi (3,5 - 105 bar), 200 psi (14 bar) Standard Setting
<b>N</b>	Seal Material	Buna-N
<b>(none)</b>	Material/Coating	Standard Material/Coating

### TECHNICAL DATA

NOTAR: LOS DATOS PUEDEN VARIAR SEGÚN LA CONFIGURACIÓN . CONSULTE LA SECCIÓN DE CONFIGURATION

Factory Pressure Settings Established at	blocked control port (dead headed)
Maximum Operating Pressure	350 bar
Control Pilot Flow	0,11 - 0,16 L/min.
Adjustment - No. of CW Turns from Min. to Max. setting	5
Locknut Hex Size	15 mm
Locknut Torque	9 - 10 Nm
Seal kit - Cartridge	Buna: 990011007
Seal kit - Cartridge	EPDM: 990011014
Seal kit - Cartridge	Polyurethane: 990011002
Seal kit - Cartridge	Viton: 990011006

### NOTES

- Maximum pressure differentials for spring ranges: A and B are 3000 psi (210 bar) N and Q are 2000 psi (140 bar) W is 5000 psi (350 bar) inlet pressure
- For Series 1 cartridges configured with an O control (panel mount handknob), a .75 in. (19 mm) diameter hole is required in the panel.

### CONFIGURATION OPTIONS

#### Model Code Example: PBDBMBN

CONTROL	(M) ADJUSTMENT RANGE	(B) SEAL MATERIAL	(N) MATERIAL/COATING
<b>M</b> Capped Screw Adjustment with Lockwire Holes	<b>B</b> 50 - 1500 psi (3,5 - 105 bar), 200 psi (14 bar) Standard Setting	<b>N</b> Buna-N <b>V</b> Viton	Standard Material/Coating /AP Stainless Steel, Passivated /LH Mild Steel, Zinc-Nickel
<b>L</b> Standard Screw Adjustment	<b>A</b> 100 - 3000 psi (7 - 210 bar), 200 psi (14 bar) Standard Setting		
<b>C</b> Tamper Resistant - Factory Set	<b>W</b> 150 - 4500 psi (10,5 - 315 bar), 200 psi (14 bar) Standard Setting		
<b>K</b> manilla	<b>N</b> 60 - 800 psi (4 - 55 bar), 200 psi (14 bar) Standard Setting		
<b>W</b> Hex Wrench Adjustment	<b>Q</b> 60 - 400 psi (4 - 28 bar), 200 psi (14 bar) Standard Setting		
<b>Y</b> manilla de tres agarres			